



imagePROGRAF
PRO-6000S/4000S
PRO SERIES

QUALITY, QUANTITY, SPEED. A NEW ERA OF LARGE-FORMAT PRINTING.



imagePROGRAF PRO-6000S/4000S

TECHNICAL INFORMATION

PRINT		GENERAL	
Printing Technology	FINE: Full-Photolithography Nozzle Engineering	Interfaces	Hi-Speed USB, 10/100/1000Base-T/TX, Wi-Fi
Head Configuration	12-Channel Integrated Type	Printer Language	SGRaster
Nozzle Pitch	600 dpi x 2	Recommended Operating Environment	Temperature: 59° - 86° F (15° - 30° C) Humidity: 10 - 80% (No Condensation)
Nozzle Configuration	1,536 Nozzles x 12 Channels: 18,432 Total	Power Supply	AC 100-240 V (50-60 Hz)
Droplet Size	4 Picoliters per Color	Power Consumption	PRO-6000S Maximum: 113 W or Less PRO-4000S Maximum: 107 W or Less Standby: 1.8 W or Less Power Off: 0.5 W or Less
Maximum Print Resolution	Up to 2400 x 1200 dpi	Printing Software	imagePROGRAF Printer Driver, Print Studio PRO**, Print Plug-In for Microsoft Office, Digital Photo Professional, PosterArtist Lite
Ink Information	Type: Pigment-Based LUCIA PRO Ink Technology PFI-1100 (160 ml): PBK, MBK, C, M, Y, PC, PM, GY PFI-1300 (330 ml): PBK, MBK, C, M, Y, PC, PM, GY PFI-1700 (700 ml): PBK, MBK, C, M, Y, PC, PM, GY	Optional Software	PosterArtist
PRINTER SPECS		OS Compatibility	32-bit: Windows® Vista/7/8/8.1/10 64-bit: Windows® Vista/7/8/8.1/10 Mac: OS X 10/7.5-10.11
Print-Head	PF-10 (I)	Utilities	Accounting Manager, Device Management Console, Media Configuration Tool, Quick Utility Toolbox
Colors	Photo Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Gray	User-Replaceable Items	Print-Head (PF-10) Maintenance Cartridge (MC-30) Rotary Cutter (CT-07)
Ink Tank Shipped with Printer	8 Colors: MBK/C/M/Y (330 ml Starter Tank, Each Color) PBK/PC/PM/GY (190 ml Starter Tank, Each Color)	Options	PRO-6000S : Roll Holder Set (RH2-65) PRO-4000S : Roll Holder Set (RH2-45) PRO-4000S : Multifunction Roll System (RU-41)
Hard Disk Capacity	320 GB	* The maximum printable length varies, depending on the application, OS, and RIP used.	
Printer Memory	1 GB	** Print Studio PRO plug-in software is compatible with Adobe Photoshop CS5/CS6/CC/CC (2014)/CC (2015), Adobe Photoshop Elements 11/12/13, Adobe Photoshop Lightroom 3/4/5/6, and Canon Digital Professional 3.12 or later.	
Printer Stand	Standard	PRELIMINARY INFORMATION	
Display	3.5" Color LCD Touch-screen		
Size/Weight (with basket open)	PRO-6000S : 46.0" (H) x 78.7" (W) x 38.7" (D) /302 lb. PRO-4000S : 46.0" (H) x 62.7" (W) x 38.7" (D) /267 lb.		
MEDIA			
Media Feed	PRO-6000S : Front-Loading Roll Feed: Two Rolls, Front Output PRO-4000S : Front-Loading Roll Feed: One Roll, Front Output Front-Loading Manual Feed: Front Loading, Front Output		
Media Width	PRO-6000S : 8" - 60" (Cut-Sheet and Roll) PRO-4000S : 8" - 44" (Cut-Sheet and Roll)		
Minimum Media Length	8"		
Maximum Print Length*	59" (Roll Paper) 63" (Cut-Sheet)		
Borderless Printing Widths	PRO-6000S : 10"/14"/17"/24"/36"/42"/44"/50"/54"/60" PRO-4000S : 10"/14"/17"/24"/36"/42"/44"		
Media Thickness	.07 mm - .08 mm		
Media Core Sizes	2" or 3" Core (with Supplied Adaptor)		
Printable Margins	Roll Paper: Top: 3 mm; Bottom: 3 mm; Side: 3 mm Cut-Sheet: Top: 3mm; Bottom: 20mm; Side: 3 mm		
Maximum Media Roll (Outer Dia.)	6.7" (170 mm)		

 USA.CANON.COM/LARGEFORMAT



Canon and imagePROGRAF are registered trademarks and LUCIA PRO is a trademark of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Some items may not be available at this time, please check for availability. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2016 Canon U.S.A., Inc. All rights reserved.

0216-6000S/4000S OF-1M-BJA

